

n accordance with International Standards for safety transformers

GUARANTEED

MARSHAL **POWER CONTROL UNI**

For the control of

low-voltage D.C. Motors

For use with A.C. mains supply only Input 220/250 volts 50/60 cycles Two Outputs:

- A 12 volts DC (controlled) for operating a tractive-type motor
- B. 15 volts A.C. for operating motivated accessories or accessories equipped for lighting.

SHORT-CIRCUIT PROOF ● SHOCK PROOF

- Suitable for use on all domestic wiring systems (two-pin, three-pin and ordinary light sockets) with COMPLETE SAFETY. Earthing is not necessary
- Built to withstand misuse, both outputs may be loaded to any extent without risk to the unit or user
- Positive voltage control. Printed circuit.
- Incorporates new safety transformer of unique design, which is inherently protected.
- Indestructible diecast case, totally enclosed and rivet sealed for absolute safety.
- Supply cord is moisture-proof.
- Double checked, inspected, and tested for operational ability, insulation, and short-circuit protection.
- Individually tested to withstand 5,000 volts between input circuit and case.
- The only power control unit in its class with Double Insulation
- The insulation resistance is ten times greater than that usually associated with domestic wiring installations.
- This unit will operate in any position.
- Built in the MECCANO tradition, ensuring safety, reliability and satisfaction.
- Overall dimensions $7'' \times 4\frac{1}{2}'' \times 2\frac{7}{8}''$

For use with A.C. mains supply only Input 230/250 volts 50/60 cycles Three Outputs:

A 12 volts D.C. (controlled) for operating a tractive-type motor. Pulse power is available over the full range of control on this output.

B. 15 volts A.C. for accessories.

C. 15 volts A.C. for special accessories and/or separate controller. output is completely isolated assuring independent control.

SHORT-CIRCUIT PROOF ● SHOCK PROOF

Suitable for use on all domestic wiring systems (2-pin, 3-pin and ordinary light sockets) with COMPLETE SAFETY. Earthing is not necessary.

Built to withstand misuse, all outputs may be loaded to any extent without risk to the unit or user

Positive voltage control. Printed circuit.

Incorporates new safety transformer of unique design, which is inherently protected.

Indestructible diecast case, totally enclosed and rivet-sealed for absolute safety.

Supply cord is moisture-proof.

Double checked, inspected, and tested for operainsulation and short-circuit tional ability, protection

Individually tested to withstand 5,000 volts

between input circuit and case.

The only power control unit in its class with Double Insulation.

The insulation resistance is ten times greater than that usually associated with domestic wiring installations.

This unit will operate in any position. Pulse power on output "A" provides ultra-slow speed control at the touch of a switch.

Built in the MECCANO tradition, ensuring safety, reliability and satisfaction.

Overall dimensions $6\frac{7}{8}$ \times $6\frac{3}{8}$ \times $3\frac{7}{8}$

AVAILABLE EARLY 1960

Price 75/-

n accordance with International Standards for safety transformers

★ GUARANTEED FOR 2 YEARS